

# 2018 RENEGADE™ X XC 650 T3B ABS

## HIGHLIGHTS

- Rotax® V-twin engine
- Anti-Lock Brake System (ABS)
- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Continuously Variable Transmission (CVT)
- Tri-Mode Dynamic Power Steering (DPS™)
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshoot† ATR tires
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent (TTI) rear suspension
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



White, Black & Can-Am red / 650

## ENGINES

	650
Type	62 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Maximum Speed	105km/h

## SUSPENSIONS

Front Suspension	Double A-arm 22.9 cm (9 in.) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm (9.3 in.) travel
Rear Shocks	FOX 1.5 PODIUM RC2

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

## TIRES / WHEELS

Front Tires	ITP Holeshoot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshoot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlocks

## DIMENSIONS / CAPACITIES

L x W x H	218.4 x 116.8 x 124 cm (86 x 46 x 48.8 in.)
Wheelbase	129.5 cm (51 in.)
Ground Clearance	26.7 cm (10.5 in.)
Seat Height	87.7 cm (34.5 in.)
Dry Weight*	303 kg
Rack Capacity	Rear: 16 kg
Storage Capacity	N/A
Towing Capacity	660 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5 L

## FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
T3B features	Towing hitch with trailer plug, directional indicator, position lamps, mirrors, horn, lockable fuel cap and transmission	Seat	Standard
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
		Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, aluminum skid plate, mudguards

## WARRANTY

Factory	2 years
---------	---------

**BRP** ©2017 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

**can-am**

Can-AmOffroad.com

