

# 2019 MAVERICK™ TRAIL 800 T

## HIGHLIGHTS

### AGILE

- Sturdy engine and transmission
- Easy Handling and capabilities
- Front and rear suspension designed for trail riding

### ADVENTUROUS

- Meaningful functionality and versatility
- Enhanced comfort with Ergo-Lok cockpit
- Build your Maverick Trail that fits your needs

### CONFIDENT

- Can-Am design and proven fit & finish
- Enhanced protection
- More adventure and less maintenance

### SPECIFIC TO PACKAGE

- Visco-Lok† auto-locking front differential
- 12-in. steel wheels
- Ergoprint seats

## ENGINES

### 800

Type	55 hp, Rotax® 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control
Power Steering	N/A
Speed category	Up to 60 km/h

## SUSPENSIONS

Front Suspension	Double A-arm with sway bar 25.4 cm travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar 26.7 cm travel
Rear Shocks	Twin tube gas charged shocks

## BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

## FEATURES

Gauge	7.6" wide multifunction digital display	Winch	Prewired for available winch
Instrumentation	Lighter type DC outlet in console (20-A)	Steering Wheel	Adjustable tilt steering
Magneto	650W	Protection	Integrated front steel bumper, injected full body skid plates, mudguards, mudflaps
Lighting	Two 55 W reflectors and LED tail lights	Hitch Type	2-in. hitch receiver with tow ball, 7-pin trailer connection (12V)
T-category features	Horn, flashers and position lamps, mirrors, hook on front metal bumper		

## WARRANTY

Factory	2 years
---------	---------



White

## TIRES / WHEELS

Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12-in. steel

## DIMENSIONS / CAPACITIES

L x W x H	300.5 x 127 x 175.5 cm
Wheelbase	230.1 cm
Ground Clearance	25.4 cm
Dry Weight	596 kg
Cage	ROPS-approved profiled cage Certified ISO 3471
Cargo Box Capacity	136 kg
Storage Capacity	Total: 20.2 L Glove Box: 15.6 L Driver storage: 1.5 L Center console and Cup holders: 3.1 L
Towing capacity	680 kg
Fuel Capacity	38 L